

ELECTRICAL CHARACTERISTICS

Contact Current Rating: 1 Amp
 Dielectric Withstanding Voltage: 500V AC
 Insulation Resistance: 500MΩ/Min
 Contact Resistance: 35mΩ/Max
 Operation Temperature: -25°C ~ +85°C

7	HOOD	PBT+30%GF	COLOR:BLACK	
6	SCERW	STEEL	PLATING:NI	L=33mm
5	CLAMP	STEEL	PLATING:MATTE TIN AND NI	
4	COVER	PBT+30%GF	COLOR:BLACK	
3	HOUSING	PBT+30%GF	COLOR:BLACK	
2	SHELL	SPCC	PLATING:NI	
1	TERMINAL	COPPER ALLOY	CONTACT AREA: Au 3u" SOLDER AREA: G/F UNDER-PLATING: NI	

ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS
------	-------	----------	---------	--------------

QUALITY SYMBOLS


□ :
 MAJOR

△ :
 CRITICAL

▽ :
 ZERO DEFECT S.P.C

Tolerance

±0.80
 ±0.50
 ±0.30



NAME:	3M同等品 SCST 26P MALE SOLDER ASSEMBLY (客户用图)	PART NO.	B01-02631134-01
REV:	B	DRW BY	CHK BY
SCALE:	N:1	DATE:	2009/06/11
		DAW	NHU
			KING ZHOU

REV:	B	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
SCALE:	N:1	DATE:	2009/06/11	DAW	NHU		B01-013

东莞市箐国电子有限公司

△	2017/10/12	依新开模具变更外壳尺寸,修正温度参数	HP GUAN	QUALITY SYMBOLS
△	2009/06/11	新版发行	King Zhou	CRITICAL MAJOR
△	DATE	DESCRIPTION	APPROVER	ZERO DEFECT S.P.C

8	7	6	5	4	3	2	1
---	---	---	---	---	---	---	---