



**• ELECTRICAL CHARACTERISTICS**  
 Contact Current Rating: 1 Amp  
 Dielectric Withstanding Voltage: 500V AC  
 Insulation Resistance: 500MΩ/Min  
 Contact Resistance: 35mΩ/Max  
 Operation Temperature: -25°C ~ +85°C

5	LATCH	SUS 304			
4	HOOD	ABS	COLOR: GRAY		
3	HOUSING	PBT+30%GF	COLOR: BLACK		
2	SHELL	SPCC	PLATING: Ni		
1	TERMINAL	COPPER ALLOY	CONTACT AREA: G/F SOLDER AREA: Sn UNDER-PLATING: Ni		

QUALITY SYMBOLS

□ : MAJOR

△ : CRITICAL

▽ : ZERO DEFECT

Tolerance

X : ±0.80

x : ±0.50

.xx : ±0.30



NAME:

SW 6P MALE SOLDER何服连接器 (客户用图)

PART NO.

B01-006321A1-01

REV:

A

UNIT:

mm

DRW BY

CHK BY

APP BY

APP BY

APP BY

DRAWING NO.

B01-006

SCALE:

N:1

DATE:

2016/07/14

DAW NHU

KING ZHOU

KING ZHOU

KING ZHOU

KING ZHOU

KING ZHOU

KING ZHOU

东莞市箐国电子有限公司

APPROVER

King Zhou

DESCRIPTION

DATE

2016/07/14

DATE

2016/07/14

DATE

DATE

DATE

DATE

DATE

DATE

DATE

8

7

6

5

4

3

2

1

8

7

6

5

4

3

2

1