



剖面
A-A

上盖

下盖

ELECTRICAL CHARACTERISTICS

Contact Current Rating: 1 Amp
 Dielectric Withstanding Voltage: 500V AC
 Insulation Resistance: 500MΩ/Min
 Contact Resistance: 35mΩ/Max
 Operation Temperature: -25°C ~ +105°C

7	HOOD	ABS+30%GF	COLOR: GRAY
6	SCREW	STAINLESS STEEL	
5	WRENCH SPRING	STAINLESS STEEL	
4	COVER	PBT+30%GF	COLOR: BLACK
3	HOUSING	PBT+30%GF	COLOR: BLACK
2	SHELL	SPCC	PLATING: NI
1	TERMINAL	COPPER ALLOY	CONTACT AREA: Au 3u" SOLDER AREA: G/F UNDER-PLATING: NI

QUALITY SYMBOLS

□ :
 CRITICAL

☒ :
 MAJOR

▽ :
 ZERO DEFECT

Tolerance

X: ±0.80

x: ±0.50

.xx: ±0.30

NAME:	PQR-20F伺服连接器				PART NO.:	B01-02042134-01	
REV.:	A	UNIT:	mm	DRW BY:	CHK BY:	APP BY:	DRAWING NO.:
SCALE:	N:1	DATE:	2013/01/09	JING LI	JACK CHEN		B01-009

东莞市箐国电子有限公司

