



- Current Rating: 1 Amp
- Insulation Resistance: 500MΩ/Min
- Withstanding Voltage: 500V AC/Min
- Contact Resistance: 35mΩ Max
- Temperature Range: -25°C ~ +85°C

6	BOARDLOCK	COPPER ALLOY	PLATING: Tin	
5	BRACKET	SPCC	PLATING: Ni	
4	COVER	LCP+30%GF	COLOR: BEIGE	
3	HOUSING	LCP+30%GF	COLOR: BEIGE	
2	SHELL	SPCC	PLATING: Ni	
1	TERMINAL	PHOSPHOR BRONZE	CONTACT AREA: Au 5u" SOLDER AREA: Sn UNDER-PLATING: Ni	

QUALITY SYMBOLS

□ :  :

CRITICAL MAJOR

▽ :  :

ZERO DEFECT S.P.C

Tolerance	NAME:	CIS00(1.0mm) 28P FEMALE R/A Type DOUBLE	PART NO.	B06-0528C1ED-01
±0.50	REV:	A	CHK BY	APP BY
±0.30	SCALE:	N:1	DATE:	2013/03/07
±0.25				

A	DATE	2013/03/07	DESCRIPTION	NEW ISSUE	APPROVER	JINGLI
8	SIDE	DATE	DESCRIPTION	NEW ISSUE	APPROVER	JINGLI

东莞市箜国电子有限公司

DRAWING NO.	B06-007
-------------	---------