



Voltage Current Rating: 0.3 AMP.
 Dielectric Withstanding Voltage: 250V AC
 Contact Resistance: 100 mΩ Max.
 Insulation Resistance: 500MΩ Min.
 Temperature Range: -20°C to +85°C

NO.	MATERIAL	QTY	MATERIAL	PLATING & COLOR
I	SHIELD	2	zinc alloy	Ni: 80u"Min
H	CABLE CLIPPER	1	SPCC T=0.80mm	Ni: 80u"Min
G	FLAT SOREW	2	SPCC	Ni: 80u"Min
F	FLAT SOREW	4	SPCC	Ni: 80u"Min
E	LONG CONTACT	13	C2680-EH T=0.30mm	90U PLAS PLATING ON CONTACTS 80U FULL OVER NICKEL PLATING
D	SHORT CONTACT	13		
C	SHELL	1	SPCC T=0.30mm	Ni: 80u"Min
B	COVER	1	LCP+15%GF UL94-V0	BLACK
A	INSULATOR	1	LCP+15%GF UL94-V0	BLACK

QUALITY SYMBOLS	Tolerance	NAME:	PART NO.
□: <input type="checkbox"/>	±0.80	SDR-26P Male Solder Connector	B06-026111AA-02
⊗: <input type="checkbox"/>	±0.50	REV: A	DRW BY
MAJOR	±0.30	UNIT: mm	CHK BY
MINOR	±0.30	SCALE: N:1	DATE: 2018/01/09
CRITICAL		JING LI	JACK CHEN
MAJOR			
MINOR			
ZERO DEFECT			
S.P.C			

DATE	DESCRIPTION	APPROVER	SIDE
2018/01/09	新版发行	JACK CHEN	8
			7
			6
			5
			4
			3
			2
			1

东莞市箐园电子有限公司

B01-009