



Voltage Current Rating: 1.5 AMP, 40V AC
 Dielectric Withstanding Voltage: 500V AC
 Contact Resistance: 30 mΩ Max.
 Insulation Resistance: 100MΩ Min.
 Temperature Range: -25°C to +85°C

4	COVER	ABS UL94V-0	COLOR: BLACK	
3	SCREW+NUT	STEEL	OVER-PLATING: NI	
2	HOUSING	PBT UL94V-0	COLOR: BLACK	
1	CONTACT	COPPER ALLOY	CONTACT AREA: G/F SOLDER AREA: G/F UNDER-PLATING: NI	

QUALITY SYMBOLS

□: MAJOR

△: CRITICAL

▽: ZERO DEFECT

Tolerance

±0.50

±0.30

±0.10

NAME: FCN-40P Female Connector (A6CONH)

REV: B

SCALE: NONE

DATE: 2011/07/02

UNIT: mm

DRW BY: JING LI

CHK BY: JACK CHEN

APP BY: B01-040

PART NO. B01-04041NB-01

REMARKS

PART REMARKS

DRAWING NO. B01-040

APPROVER: JING LI

DATE: 2011/07/02

DESCRIPTION: 新版发行

SIDE: 8

8

7

6

5

4

3

2

1

东莞市箐国电子有限公司