



High Power Contact Current Rating:  
10,20 or 40AMPS  
High Power Contact Resistance:  
2.7 Milliohms Max.  
Dielectric Withstanding Voltage:  
1000V AC For 1 Minute  
Insulation Resistance:5000MΩ Min.  
Temperature Range:-25°C to +85°C

PART NO.:

B08-2W231140-X1

CURRENT RATING&DIMENSION ØA: \_\_\_\_\_

A:10 AMPS Ø 1.70mm  
B:20 AMPS Ø 2.80mm  
C:30 AMPS Ø 3.20mm  
D:40 AMPS Ø 4.60mm

4	HOUSING	PBT+30%GF	COLOR:BLACK	
3	FRONT PLASTIC	STEEL	OVER-PLATING:Sn	
2	FRONT SHELL	STEEL	OVER-PLATING:NI	
2	HIGH POWER CONTACT	BRASS	PLATING:AU G/F	
1	SIGNAL CONTACT	BRASS	PLATING:AU G/F	

QUALITY SYMBOLS

□ :  MAJOR

△ :  CRITICAL

▽ :  ZERO DEFECT

Tolerance

x. ±0.50

.x ±0.30

.xx ±0.30

NAME: High-Power 2W2 Mdle Solder Type

REV: A UNIT: mm

SCALE: NONE DATE: 2012/05/20

DRW BY: DAW NHU

PART NO. B08-2W231140-X1

APP BY: KING ZHOU

DRAWING NO. 1198-022

东莞市箐国电子有限公司

8	7	6	5	4	3	2	1
DATE	DESCRIPTION	APPROVER	ZERO DEFECT	S.P.C			
△							
△							
△							
SIDE							