

High Power Contact Current Rating:  
10,20 or 40AMPS  
High Power Contact Resistance:  
2.7 Milliohms Max.  
Dielectric Withstanding Voltage:  
1000V AC For 1 Minute  
Insulation Resistance:5000MΩ Min.  
Temperature Range:-25°C to +85°C

PART NO: B08-3W35114D-X1

Current Rating: \_\_\_\_\_  
A = 10 AMPS Dim.A Ø1.7 Dim.B Ø2.2  
B = 20 AMPS Dim.A Ø2.8 Dim.B Ø3.3  
C = 30 AMPS Dim.A Ø3.2 Dim.B Ø3.7  
D = 40 AMPS Dim.A Ø3.7 Dim.B Ø4.2

PCB LAYOUT

ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS
6	JACKSCREWS	BRASS	PLATING: NI	
5	HOUSING	PBT+30%GF	COLOR: WHITE	
4	RIVETED INSERT	BRASS	PLATING: NI	
3	REAR SHELL	SPCC	PLATING: Sn	
2	FRONT SHELL	SPCC	PLATING: NI	
1	TERMINAL	BRASS	TERMINAL FINISH: FULL GOLD FINISHED 2U"	

QUALITY SYMBOLS

□ :  : MAJOR

△ :  : CRITICAL


▽ :  : ZERO DEFECT S.P.C

Tolerance

X. ±0.50

.X ±0.30

.XX ±0.25



NAME:	3W3 Male R/A Type With Bracket+Nut				PART NO.	B08-3W35114D-X1	
REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
SCALE:	N:1	DATE:	2017/01/05	JINGLI	KING ZHOU		B08-025

东莞市箐国电子有限公司

