



Rev	Date	Description	B.Y.	ECN NO.
A0	2017.05.22	New Drawing	Owen	

NOTE:

1. MATERIAL:
 - 1.1 INSULATOR:PBT BLACK UL 94V-0
 - 1.2 COVER:LCP BLACK UL94-V0
 - 1.3 CONTACT: COPPER ALLOY(T=0.30mm)
 - 1.4 SHELL: Zinc alloy.

2. ELECTRICAL CHARACTERISTICS:

- 2.1 CONTACT RATING:30 VAC
- 2.2 CONTACT CURRENT RATING:0.5A
- 2.3 DIELECTRIC WITHSTANDING VOLTAGE:500V AC FOR 60S
- 2.4 INSULATION RESISTANCE 500mΩ MIN INITIAL
- 2.5 OPERATING TEMPERATURE:-45°C ~ 85°C

4. PLATING

- 4.1 TERMINAL:50u" MIN NICKEL ALL OVER
80u" MIN Tin ON SOLDER AREA
30u" GOLD ON CONTACT AREA
- 4.2 SHELL:100u"MIN,NICKEL OVER 50"MIN COPPER

5. Ordering information:

B03-XXX - 618 X 7-01
(1)

- (1): No. of Contacts:
 - 014=14pins 020=20pins
 - 026=26pins 036=36pins
 - 050=50pins 068=68pins
- (2): Contact Finishes:
 - A=Gold Flash Selective Plating
 - C=3u" Gold Selective Plating
 - H=15u" Gold Selective Plating

-TOLERANCES- UNLESS OTHERWISE SPECIFIED		Title: SCSI CN-26P Female 90° DIP			
0. =±.40	0.° =±3.0°	Appd: <i>B.X.T</i>	P/N: B03-026618X7-01		
0.0 =±.35	0.0° =±2.5°	Check: <i>B.X.T</i>	Date	Scale	Unit
0.00=±.3	0.00° =±2.0°	Draw.: <i>DL</i>	2017.05.22	Free	MM
					Z
					Page
					1/1

东莞市誉国电子有限公司