



PIN ASSIGNMENT

P1	SIGNAL	P2
1		1
2		2
3		3
4~47		4~47
48		48
49		49
50		50
Shell		Shell

NOTES:

1. ELECTRICAL TEST: 100% OPEN, SHORT & MISS WIRE TEST.
2. CONDUCTOR RESISTANCE: 5 OHMS MAX.
3. INSULATOR RESISTANCE: 1M OHMS MIN, DC 300V 0.01sec.
4. THIS PRODUCT MEET ROHS STANDARD ENVIRONMENTAL PROTECTION POLICY.

QUALITY SYMBOLS
 ■ : CRITICAL
 □ : MAJOR
 ▽ : ZERO DEFECT S.P.C



UNIT: mm
 SCALE: 2:1
 TOLERANCES: DIM. ±0.10
 ANGLE: ±1°

东莞市箐国电子有限公司

REV	DESCRIPTION	DATE
A	圖面發行	2016-05-22

Part NO	LENGTH	REMARK
1 FC-DB50-01C	L=1000MM	
2 FC-DB50-02C	L=2000MM	
3 FC-DB50-03C	L=3400MM	
4 FC-DB50-04C	L=6400MM	

ITEM	PART NAME	DESCRIPTION	QTY
1	CONNECTOR	HPCN SCSI 50Pin Male CONNECTOR ASS'Y TYPE	2SET
2	CABLE	UL20276 28AWG*25P+ABD PVC JACKET COLOR:BLACK OD= 8.6mm	1PCS
3	TUBE	Heat-shrink tube Black DD=10.0MM L=15MM	2PCS

APPROVED	CHECKED	DESIGN	DRAWN	PART NO.	FC-DB50-XXC	SHT	1/1
				SCSI-II 50Pin CABLE			

DRAWING NO.	FC-DB50	REV	A