



- NOTES:
- ELECTRICAL:
 - CONTACT RESISTANCE :25mΩ MAX
 - WITHSTANDING VOLTAGE :500V AC FOR ONE MINUTE
 - INSULATION RESISTANCE :500MΩ MIN
 - VOLTAGE CURRENT RATING :1.00 AMP
 - ENVIRONMENTAL:
 - OPERATION TEMPERATURE:-55°C~+105°C

| | | | | |
|------|--------------|------------|--|----------|
| ⑤ | BOARD LOCK | BRASS | 2.5um Tin plated over- 1.25um nickel under- | 2 |
| ④ | CONTACT | C5191-H | (Pd+Au)0.375um Au plated on Contact Area;2.5um Tin plated on soldering end ,over 1.25um nickel under-plating | 50 |
| ③ | BRACKET | ZINC ALLOY | 1.25um nickel plated | 1 |
| ② | COVER | PBT+30%G/F | | 1 |
| ① | HOUSING | PBT+30%G/F | | 1 |
| ITEM | DESCRIPTIONS | MATERIAL | FINISH | QTY NOTE |

| | | | | | |
|-------------|---------|-----------|-----|--|--|
| TOLERANCE : | | TEL | | 东莞市誉国电子有限公司 | |
| X: ± 0.30 | X': ±2° | APPROVALS | FAX | PART NO. B02-05061HC-JL | |
| .X ± 0.20 | X: ±1° | DRAWN | | TITLE SCST-II 50P Female R/A DIP Type (J1) | |
| .XX ± 0.05 | | CHECKED | | SCALE 1:1 UNIT MM SHEET 1/1 | |
| | | APPROVED | | | |

| | | | | | | | | | |
|------|----------|-------------|--------|----------|----------------------|--------------|-------|------|-------|
| REV. | ECN. NO. | DESCRIPTION | ISSUED | APPROVED | 3rd ANGLE PROJECTION | CONFIDENTIAL | SCALE | UNIT | SHEET |
| 1 | | | | | | | 1:1 | MM | 1/1 |