



PCB Layout (B)

- Current Rating: 1 Amp
- Insulation Resistance: 500MΩ/Min
- Withstanding Voltage: 500V AC/Min
- Contact Resistance: 35mΩ Max
- Temperature Range: -25°C ~ +85°C

6	BOARDLOCK	COPPER ALLOY	PLATING: Tin	
5	BRACKET	SPCC	PLATING: Ni	
4	COVER	PBT+30%GF	COLOR: BLACK	
3	HOUSING	PBT+30%GF	COLOR: BLACK	
2	SHELL	SPCC	PLATING: Ni	
1	TERMINAL	PHOSPHOR BRONZE	CONTACT AREA: Au 5u" SOLDER AREA: Sn UNDER-PLATING: Ni	

ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS
------	-------	----------	---------	--------------

QUALITY SYMBOLS		Tolerance
□ :	CRITICAL	X. ±0.50
☒ :	MAJOR	.X ±0.30
▽ :	ZERO DEFECT S.P.C	.XX ±0.25

NAME:	SCSI-II 20Pin Female R/A DIP Type		PART NO.	B02-020611IC-2S
REV:	A	UNIT: mm	CHK BY	APP BY
SCALE:	N:1	DATE: 2012/07/08	JINGLI	KING ZHOU

APPROVER	JINGLI
----------	--------

DESCRIPTION	NEW ISSUE
-------------	-----------

DATE	2012/07/08
------	------------

SIDE	8	7	6	5	4	3	2	1
<h2>东莞市箐围电子有限公司</h2>								
DRAWING NO.	B02-004							