

8	7	6	5	4	3	2	1	1																									
F	<table border="1"> <thead> <tr> <th>No. of Contact</th> <th>A</th> <th>B</th> <th>C</th> <th>D</th> </tr> </thead> <tbody> <tr> <td>15</td> <td>16.3</td> <td>25.0</td> <td>30.8</td> <td>19.3</td> </tr> <tr> <td>26</td> <td>24.6</td> <td>33.3</td> <td>39.1</td> <td>27.5</td> </tr> <tr> <td>44</td> <td>38.3</td> <td>47.0</td> <td>53.0</td> <td>41.3</td> </tr> <tr> <td>62</td> <td>54.8</td> <td>63.5</td> <td>69.3</td> <td>57.7</td> </tr> </tbody> </table>								No. of Contact	A	B	C	D	15	16.3	25.0	30.8	19.3	26	24.6	33.3	39.1	27.5	44	38.3	47.0	53.0	41.3	62	54.8	63.5	69.3	57.7
No. of Contact	A	B	C	D																													
15	16.3	25.0	30.8	19.3																													
26	24.6	33.3	39.1	27.5																													
44	38.3	47.0	53.0	41.3																													
62	54.8	63.5	69.3	57.7																													
E																																	
D	<p>Voltage Current Rating: 5 AMP. Dielectric Withstanding Voltage: 1000V AC Insulation Resistance: 1000MΩ Min. Temperature Range: -25°C to +85°C</p> <p>PART NO: B04-0XX4X14N-02</p> <p>NO. OF CONTACT: 15 = 15 pos 26 = 26 pos 44 = 44 pos 62 = 62 pos</p> <p>HOUSING COLOR: 1 = BLACK 5 = WHITE 6 = BLUE</p>																																
C																																	
B	<table border="1"> <thead> <tr> <th>ITEM</th> <th>DESC.</th> <th>MATERIAL</th> <th>REMARKS</th> <th>PART REMARKS</th> </tr> </thead> <tbody> <tr> <td>4</td> <td>REAR SHELL</td> <td>SPCC</td> <td>PALTING: Sn</td> <td></td> </tr> <tr> <td>3</td> <td>FRONT SHELL</td> <td>SPCC</td> <td>PALTING: Ni</td> <td></td> </tr> <tr> <td>2</td> <td>HOUSING</td> <td>PBT+30%GF</td> <td>COLOR: SEE PART NO. CONTACT AREA: G/F</td> <td></td> </tr> <tr> <td>1</td> <td>TERMINAL</td> <td>COPPER ALLOY</td> <td>SOLDER AREA: Sn</td> <td></td> </tr> </tbody> </table>								ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS	4	REAR SHELL	SPCC	PALTING: Sn		3	FRONT SHELL	SPCC	PALTING: Ni		2	HOUSING	PBT+30%GF	COLOR: SEE PART NO. CONTACT AREA: G/F		1	TERMINAL	COPPER ALLOY	SOLDER AREA: Sn	
ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS																													
4	REAR SHELL	SPCC	PALTING: Sn																														
3	FRONT SHELL	SPCC	PALTING: Ni																														
2	HOUSING	PBT+30%GF	COLOR: SEE PART NO. CONTACT AREA: G/F																														
1	TERMINAL	COPPER ALLOY	SOLDER AREA: Sn																														
A	<p>QUALITY SYMBOLS</p> <p>□ : CRITICAL ☒ : MAJOR ▽ : ZERO DEFECT S.P.C</p> <p>Tolerance</p> <p>X: ±0.50 X: ±0.30 .XX: ±0.25</p>																																
A	<p>NAME: HD.-SUB 传统母头焊线式 (车针) PART NO. B04-0XX4X14N-02</p> <p>REV: A UNIT: mm DRAWN BY: KING ZHOU CHK BY: APP BY</p> <p>SCALE: N:1 DATE: 2007/10/16 JINGLI</p> <p>DATE: 2007/10/16 APPROVER: JINGLI</p> <p>DESCRIPTION: NEW ISSUE</p>																																
SIDE	<p>DATE: 2007/10/16</p> <p>DESCRIPTION: NEW ISSUE</p> <p>APPROVER: JINGLI</p> <p>DESCRIPTION: NEW ISSUE</p>																																
8	<p>DATE: 2007/10/16</p> <p>DESCRIPTION: NEW ISSUE</p> <p>APPROVER: JINGLI</p>																																
8	<p>DATE: 2007/10/16</p> <p>DESCRIPTION: NEW ISSUE</p> <p>APPROVER: JINGLI</p>																																
8	<p>DATE: 2007/10/16</p> <p>DESCRIPTION: NEW ISSUE</p> <p>APPROVER: JINGLI</p>																																
8	<p>DATE: 2007/10/16</p> <p>DESCRIPTION: NEW ISSUE</p> <p>APPROVER: JINGLI</p>																																
8	<p>DATE: 2007/10/16</p> <p>DESCRIPTION: NEW ISSUE</p> <p>APPROVER: JINGLI</p>																																
8	<p>DATE: 2007/10/16</p> <p>DESCRIPTION: NEW ISSUE</p> <p>APPROVER: JINGLI</p>																																
8	<p>DATE: 2007/10/16</p> <p>DESCRIPTION: NEW ISSUE</p> <p>APPROVER: JINGLI</p>																																

东莞市箐国电子有限公司

B04-005