



No. of Contact	A	B	C	D
09	16.9	25.0	30.8	19.0
15	25.3	33.3	39.2	27.7
25	39.0	47.0	53.0	41.0
37	55.4	63.5	69.4	57.3

Voltage Current Rating: 5 AMP.
 Dielectric Withstanding Voltage: 1000V AC
 Insulation Resistance: 1000MΩ Min.
 Temperature Range: -25°C to +85°C

PART NO: B05-0XX7X1AD-E5

NO. OF CONTACT:
 09 = 9 pos
 15 = 15 pos
 25 = 25 pos
 37 = 37 pos

HOUSING COLOR:
 1 = BLACK
 5 = WHITE
 6 = BLUE

ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS
6	SCREW	STEEL	PALTING: NI	
5	BOARDLOCK	COPPER ALLOY	PALTING: NI	
4	HOUSING	PBT+30%GF	COLOR: SEE PART NO.	
3	REAR SHELL	SPCC	PALTING: Sn	
2	FRONT SHELL	SPCC	PALTING: NI	
1	TERMINAL	COPPER ALLOY	CONTACT AREA: G/F SOLDER AREA: Sn UNDER-PLATING: NI	

QUALITY SYMBOLS		Tolerance	
□:	CRITICAL	x.	±0.50
⊠:	MAJOR	.x	±0.30
∇:	ZERO DEFECTS.P.C	.xx	±0.25

NAME:	D-SUB MALE 180度后脚6.0mm 叉脚间距5.0mm 螺母 (客户用图)			
REV:	A	UNIT:	mm	DRW BY
SCALE:	N:1	DATE:	2014/09/02	JINGLI
				KING ZHOU
				APP BY
				DRAWING NO.

东莞市箐国电子有限公司

DATE	2014/09/02	DESCRIPTION	NEW ISSUE	APPROVER	JINGLI
SIDE	8	DATE	7	DESCRIPTION	6