



ELECTRICAL CHARACTERISTICS

Contact Current Rating: 1 Amp
 Dielectric Withstanding Voltage: 500V AC
 Insulation Resistance: 500MΩ/Min
 Contact Resistance: 35mΩ/Max
 Operation Temperature: -55°C ~ +105°C

7	HOOD	PBT+30%GF	COLOR:BLACK	
6	SCERW	STEEL	PLATING:NI	L=33.0mm
5	CLAMP	PBT+30%GF	PLATING:MATTE TIN AND NI	
4	COVER	PBT+30%GF	COLOR:BLACK	
3	HOUSING	PBT+30%GF	COLOR:BLACK	
2	SHELL	SPCC	PLATING:NI	
1	TERMINAL	COPPER ALLOY	CONTACT AREA:3u" SOLDER AREA:5u" UNDER-PLATING:NI	

QUALITY SYMBOLS

□: CRITICAL
 ✖: MAJOR
 ▽: ZERO DEFECT S.P.C

Tolerance

X: ±0.80
 .X: ±0.50
 .XX: ±0.30

NAME: 3M同等品 SCS1 36P MALE SOLDER ASSEMBLY (客户用规格)
 TYPE:

PART NO. B01-03631134-01
 PART REMARKS

2018/12/26	依实物修正尺寸	Huaping	
2017/09/28	增加端子镀G/F规格	Huaping	
2009/06/11	新版发行	King Zhou	
DATE	DESCRIPTION	APPROVER	

REV: C	UNIT: mm	DRW BY: CHK BY: APP BY:	DRAWING NO. B01-004
SCALE: N:1	DATE: 2009/06/01	DAW NHU KING ZHOU	

东莞市箐国电子有限公司