



• ELECTRICAL CHARACTERISTICS

Contact Current Rating: 1 Amp
 Dielectric Withstanding Voltage: 500V AC
 Insulation Resistance: 500MΩ/Min
 Contact Resistance: 35mΩ/Max
 Operation Temperature: -55°C ~ +105°C

7	HOOD	PBT+30%GF	COLOR:BLACK	
6	SCERW	STEEL,L=33.0mm	PLATING:NI	
5	CLAMP	STEEL	PLATING:MATTE TIN AND NI	L=33.0mm
4	COVER	PBT+30%GF	COLOR:BLACK	
3	HOUSING	PBT+30%GF	COLOR:BLACK	
2	SHELL	SPCC	PLATING:NI	
1	TERMINAL	COPPER ALLOY	CONTACT AREA:3U ² SOLDER AREA:5u ² UNDER-PLATING:NI	

QUALITY SYMBOLS

□: :
 MAJOR

▽: :
 ZERO DEFECT S.P.C

Tolerance

X.	±0.80
X	±0.50
.XX	±0.25

NAME:	3M同等品 SCS1 50P MALE SOLDER ASSEMBLY	PART NO.	B01-0503134-01
REV.:	F	DRW BY	CHK BY
SCALE:	N:1	DATE:	2009/06/11
		DAW NHU	KING ZHOU

ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS
------	-------	----------	---------	--------------

东莞市箜国电子有限公司

2018/12/27	依模具实物修正尺寸	Huaping Guan	
2015/11/03	修正CLAMP MATERIAL	Huaping Guan	
2009/06/11	新版发行	King Zhou	
DATE	DESCRIPTION	APPROVER	

8	7	6	5	4	3	2	1
---	---	---	---	---	---	---	---