



L = 1500±30mm

P1

P2

Pin Assy

P1	Color	P2
1Pin	_____	1Pin
2Pin	_____	2Pin
3Pin	_____	3Pin
4Pin	_____	4Pin
5Pin	_____	5Pin
8Pin	_____	8Pin
6Pin	_____	6Pin
7Pin	_____	7Pin
Shell	DRAIN	Shell

- NOTES:
1. ELECTRICAL TEST: 100% OPEN, SHORT & MISS WIRE TEST.
 2. CONDUCTOR RESISTANCE: 5 OHMS MAX.
 3. INSULATOR RESISTANCE: 1M OHMS MIN, DC 300V 0.01sec.
 4. THIS PRODUCT MEET ROHS STANDARD ENVIRONMENTAL PROTECTION POLICY.

5	OVERMOLD	50P PVC CULDR. BLACK	NA
4	MOLD	PE	NA
2	CABLE	UL2919 24AWG*4SP+4EB DD-6.5MM CULDR:BLACK	1PCS
1	CONNECTOR	DIN 8Pin Male Solder TYPE Black	2PCS
ITEM	PART NAME	DESCRIPTION	QTY/T
NAME:	DIN 8Pin Male to Male Cable	PART NO.	FC-LD08MM01-1.5M

REV:	A	UNIT:	mm	DRW BY:	CHK BY:	APP BY:	DRAWING NO.:
SCALE:	N:1	DATE:	2018/03/11	Huangmei	Jack Chen		B10-037


东莞市箐国电子有限公司
 www.kinkuo.com

QUALITY SYMBOLS	Tolerance
□ : CRITICAL	x. ±0.60
⊠ : MAJOR	x. ±0.40
▽ : S.P.C	.xx ±0.25

QUALITY SYMBOLS	Tolerance
□ : CRITICAL	x. ±0.60
⊠ : MAJOR	x. ±0.40
▽ : S.P.C	.xx ±0.25

DATE	2018/03/11	DESCRIPTION	NEW ISSUE	APPROVER	Jack Chen
SIDE	8	7	6	5	4

DATE	2018/03/11	DESCRIPTION	NEW ISSUE	APPROVER	Jack Chen
SIDE	8	7	6	5	4