

L = 3000 ± 35MM

2,3,4 x 2

P1

P2

1 2 3 4

1

PIN OUT

- NOTES:
1. ELECTRICAL TEST: 100% OPEN, SHORT & MISS WIRE TEST.
  2. CONDUCTOR RESISTANCE: 5 OHMS MAX.
  3. INSULATOR RESISTANCE: 1M OHMS MIN, DC 300V 0.01sec.
  4. THIS PRODUCT MEET ROHS STANDARD ENVIRONMENTAL PROTECTION POLICY.

- 1 \_\_\_\_\_ 1
- 2 \_\_\_\_\_ 2
- 3 \_\_\_\_\_ 3
- 4 \_\_\_\_\_ 4

B		4	OVERMOLD	TPE Color: Black	A/R
		3	Hood	Ø 5.9*16mm Aluminium Alloy	2PCS
		2	CONNECTOR	3.5 Stereo PLUG (4 Poles) Au Plated	2PCS
		1	CABLE	(18/0.05 EC with Nylon filam)28AWG*4C TPE JACKET:BLACK,OD3.0mm	1PC
		No.	ITEM	DESCRIPTION	QTY

NAME:	3.5 Stereo PLUG (4 Poles) Cable	PART NO.:	FC-AV3504M01-3.0M
REV:	A	UNIT:	mm
SCALE:	N:1	DATE:	2022/11/04
		DRW BY:	Huangmei
		CHK BY:	Jack Chen
		APP BY:	
		DRAWING NO.:	AV3504-01

QUALITY SYMBOLS

□ : MAJOR

⊠ : CRITICAL

∇ : ZERO DEFECT S.P.C

Tolerance


x. ±0.60

.x ±0.40

.xx ±0.25



A		2022/11/04	NEW ISSUE	Jack Chen
△	DATE	DESCRIPTION	APPROVER	
8	7	6	5	4


**东莞市箐国电子有限公司**  
 www.KinKuo.com