



Recommended P.C.B Layout

NOTE:
1. MATERIALS:

1. HOUSING: THERMOPLASTIC, LCP UL 94V-0 RATED.
2. COVER: THERMOPLASTIC, LCP UL 94V-0 RATED.
3. CONTACTS: COPPER ALLOY, 15u" Gold on mating area. 80u" Tin on the tails.
4. SHELL: SPCC, NICKEL PLATED.
5. HARPOON: COPPER ALLOY, TIN OVER NICKEL

- 2.SPECIFICATION:
1. RATED CURRENT: 0.30A/CONTACT
 2. INSULATION RESISTANCE: 500MOHM MIN.
 3. DIELECTRIC WITHSTANDING VOLTAGE:250V AC FOR 1MINUTE.
 4. OPERATING TEMPERATURE: -25°C TO +85°C
 - 3.ROHS COMPLIANT.

PART NAME: LFH-200P Male Connector R/A DIP Type PART NO.: 71719-3501

Tolerance	QUALITY SYMBOLS
X. ±0.60	□: ☒:
X. ±0.40	CRITICAL MAJOR
.XX ±0.25	▽: ▽:
	ZERO DEFECT S.P.C

REV: A	UNIT: mm	DRW BY: Huangmei	CHK BY: Jack Chen	APP BY:	DRAWING NO. 71718
SCALE: N:1	DATE: 2023/03/20				

 东莞市箐国电子有限公司
www.kinkuo.com

A	DATE: 2023/03/20	DESCRIPTION: NEW ISSUE	APPROVER: Jack Chen
8	DATE:	DESCRIPTION:	APPROVER:

8	7	6	5	4	3	2	1
---	---	---	---	---	---	---	---