

8		7		6		5		4		3		2		1	
F															
High Power Contact Current Rating: 10.20 or 40AMPS High Power Contact Resistance: 2.7 Milliohms Max. Dielectric Withstanding Voltage: 1000V AC For 1 Minute Insulation Resistance:5000MΩ Min. Temperature Range:-25℃ to +85℃															
E															
PART NO.: B08-9W431140-X1															
CURRENT RATING&DIMENSION ϕ A:_____															
A:10 AMPS ϕ 1.70mm B:20 AMPS ϕ 2.80mm C:30 AMPS ϕ 3.20mm D:40 AMPS ϕ 4.60mm															
D															
C															
B															
A															
F															
E															
D															
C															
B															
A															
8															
7															
6															
5															
4															
3															
2															
1															

4	HOUSING	PBT+30%GF	COLOR:BLACK	
3	FRONT PLASTIC	STEEL	OVER-PLATING:Sn	
2	FRONT SHELL	STEEL	OVER-PLATING:Ni	
2	HIGH POWER CONTACT	BRASS	PLATING:Au 15u"	
1	SIGNAL CONTACT	BRASS	PLATING:G/F	

ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS
NAME: D-SUB POWER 9W4 MALE SOLDER TYPE (客户用图)				
PART NO. B08-9W431140-X1				
REV: B UNIT: mm DRW BY CHK BY APP BY				
SCALE: N:1 DATE: 2011/01/16 DAW NHU KING ZHOU				
DRAWING NO. ADA-005				

东莞市箐国电子有限公司

QUALITY SYMBOLS	Tolerance			
□: CRITICAL	±0.50	NAME:	D-SUB POWER 9W4 MALE SOLDER TYPE (客户用图)	
MAJOR	±0.30	REV:	B	UNIT: mm
MINOR	±0.15	SCALE:	N:1	DATE: 2011/01/16
ZERO DEFECT S.P.C		DAW	NHU	KING ZHOU

DATE	DESCRIPTION	APPROVER
2013/08/16	修正料号	King Zhou
2011/01/16	新版发行	King Zhou