



High Power Contact Current Rating:
 10,20 or 40AMPS
 High Power Contact Resistance:
 2.7 Milliohms Max.
 Dielectric Withstanding Voltage:
 1000V AC For 1 Minute
 Insulation Resistance:5000MΩ Min.
 Temperature Range:-25°C to +85°C

PART NO.:

B08-5W131140-X1

CURRENT RATING&DIMENSION φA: _____

A:10 AMPS φ1.70mm
 B:20 AMPS φ2.80mm
 C:30 AMPS φ3.20mm
 D:40 AMPS φ4.60mm

4	HOUSING	PBT+30%GF	COLOR:BLACK	
3	FRONT PLASTIC	STEEL	OVER-PLATING:Sn	
2	FRONT SHELL	STEEL	OVER-PLATING:NI	
2	HIGH POWER CONTACT	BRASS	PLATING:Au G/F	
1	SIGNAL CONTACT	BRASS	PLATING:Au G/F	

QUALITY SYMBOLS

□ : MAJOR

▽ : CRITICAL

▽ : ZERO DEFECT S.P.C

Tolerance

x. ±0.50

.x ±0.30

.xx ±0.30

NAME: High-Power SW1 Male Solder Type

REV: A

SCALE: NONE

DATE: 2012/05/20

UNIT: mm

DRW BY: DAW NHU

CHK BY: KING ZHOU

PART NO. B08-5W131140-X1

APP BY

DRAWING NO. 1198-022

东莞市箐国电子有限公司

8	DATE	
7	DESCRIPTION	
6	APPROVER	
5	ZERO DEFECT S.P.C	
4		
3		
2		
1		