



High Power Contact Current Rating:
10,20 or 40AMPS
High Power Contact Resistance:
2.7 Milliohms Max.
Dielectric Withstanding Voltage:
1000V AC For 1 Minute
Insulation Resistance:5000MΩ Min.
Temperature Range:-25°C to +85°C

PART NO: B08-AW56X14D-XI

HOUSING COLOR:
1:BLACK
3:GREEN
5:WHITE

CURRENT RATING:
A = 10 AMPS Dim.A ϕ 1.7 Dim.B ϕ 2.2
B = 20 AMPS Dim.A ϕ 2.8 Dim.B ϕ 3.3
C = 30 AMPS Dim.A ϕ 3.2 Dim.B ϕ 3.7
D = 40 AMPS Dim.A ϕ 3.7 Dim.B ϕ 4.2

ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS
6	JACKSCREWS	BRASS	PLATING: NI	
5	HOUSING	PBT+30%GF	COLOR: WHITE	
4	RIVETED INSERT	BRASS	PLATING: NI	
3	REAR SHELL	SPCC	PLATING: Sn	
2	FRONT SHELL	SPCC	PLATING: NI	
1	TERMINAL	BRASS	TERMINAL FINISH: FULL GOLD FINISHED 2u"	

QUALITY SYMBOLS

Tolerance

□: CRITICAL
 MAJOR
 ∇: ZERO DEFECTS.P.C

X: ±0.50
 .X: ±0.30
 .XX: ±0.25

NAME:	17W5 Female R/A Type With Bracket+Nut				PART NO.	B08-AW56114D-XI
REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY
SCALE:	N:1	DATE:	2018/09/22	JINGLI	KING ZHOU	DRAWING NO.
						B08-050

东莞市箐围电子有限公司

DATE	2018/09/22	DESCRIPTION	NEW ISSUE	APPROVER	JINGLI
SIDE	8	7	6	5	4