

	8	7	6	5	4	3	2	1																																																																							
F	39.3±0.3 35.6±0.2 6.5±0.2 1.27 1 25 26 50 9.5±0.3																																																																														
E	Contact Current Rating: 0.5 Amp Dielectric Withstanding Voltage: 500V AC/Min Insulation Resistance: 500MΩ/Min Contact Resistance: 35mΩ/Max Operaton Temperature: −45°C ~ +85°C																																																																														
D																																																																															
C	4.6±0.15 15.2±0.3																																																																														
B	<table><tr><td>4</td><td>COVER</td><td>PBT+30%G.F. (UL 94V-0)</td><td>COLOR:BLACK</td><td></td></tr><tr><td>3</td><td>HOUSING</td><td>PBT+30%G.F. (UL 94V-0)</td><td>COLOR:BLACK</td><td></td></tr><tr><td>2</td><td>SHELL</td><td>SPCC (t=0.50mm)</td><td>Ni Plating</td><td></td></tr><tr><td>1</td><td>TERMINAL</td><td>PHOSPHOR BRONZE(t=0.25mm)</td><td>CONTACT AREA: Au 50μ" SOLDER AREA: Sn 1000μ" UNDER-PLATING: Ni 50μ"</td><td></td></tr><tr><td>ITEM</td><td>DESC.</td><td>MATERIAL</td><td>REMARKS</td><td>PART REMARKS</td></tr></table>								4	COVER	PBT+30%G.F. (UL 94V-0)	COLOR:BLACK		3	HOUSING	PBT+30%G.F. (UL 94V-0)	COLOR:BLACK		2	SHELL	SPCC (t=0.50mm)	Ni Plating		1	TERMINAL	PHOSPHOR BRONZE(t=0.25mm)	CONTACT AREA: Au 50μ" SOLDER AREA: Sn 1000μ" UNDER-PLATING: Ni 50μ"		ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS																																														
4	COVER	PBT+30%G.F. (UL 94V-0)	COLOR:BLACK																																																																												
3	HOUSING	PBT+30%G.F. (UL 94V-0)	COLOR:BLACK																																																																												
2	SHELL	SPCC (t=0.50mm)	Ni Plating																																																																												
1	TERMINAL	PHOSPHOR BRONZE(t=0.25mm)	CONTACT AREA: Au 50μ" SOLDER AREA: Sn 1000μ" UNDER-PLATING: Ni 50μ"																																																																												
ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS																																																																											
A	<table><tr><td>△</td><td></td><td></td><td colspan="2">QUALITY SYMBOLS</td><td colspan="2">Tolerance</td><td colspan="2">NAME: SCS-II 100P Male Solder Type</td><td>PART NO.</td><td>B03-05031E0-01</td></tr><tr><td>△</td><td></td><td></td><td>□ :</td><td>☒ :</td><td>X.</td><td>±0.50</td><td>REV:</td><td>B</td><td>UNIT:</td><td>mm</td><td>DRW BY</td><td>CHK BY</td><td>APP BY</td><td>DRAWING NO.</td></tr><tr><td>△</td><td>2021/06/15新版发行</td><td></td><td>CRITICAL</td><td>MAJOR</td><td>.X</td><td>±0.30</td><td>SCALE:</td><td>N:1</td><td>DATE:</td><td>2021/06/15</td><td>DAMN HU</td><td>KING ZHOU</td><td></td><td>B03-0503</td></tr><tr><td>SIDE</td><td>DATE</td><td>DESCRIPTION</td><td>APPROVER</td><td>ZERO DEFECT S.P.C</td><td>▽ :</td><td>▽ :</td><td colspan="8">东莞市箐国电子有限公司</td></tr><tr><td>8</td><td>7</td><td>6</td><td>5</td><td>4</td><td>3</td><td>2</td><td>1</td><td colspan="7"></td></tr></table>								△			QUALITY SYMBOLS		Tolerance		NAME: SCS-II 100P Male Solder Type		PART NO.	B03-05031E0-01	△			□ :	☒ :	X.	±0.50	REV:	B	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.	△	2021/06/15新版发行		CRITICAL	MAJOR	.X	±0.30	SCALE:	N:1	DATE:	2021/06/15	DAMN HU	KING ZHOU		B03-0503	SIDE	DATE	DESCRIPTION	APPROVER	ZERO DEFECT S.P.C	▽ :	▽ :	东莞市箐国电子有限公司								8	7	6	5	4	3	2	1							
△			QUALITY SYMBOLS		Tolerance		NAME: SCS-II 100P Male Solder Type		PART NO.	B03-05031E0-01																																																																					
△			□ :	☒ :	X.	±0.50	REV:	B	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.																																																																	
△	2021/06/15新版发行		CRITICAL	MAJOR	.X	±0.30	SCALE:	N:1	DATE:	2021/06/15	DAMN HU	KING ZHOU		B03-0503																																																																	
SIDE	DATE	DESCRIPTION	APPROVER	ZERO DEFECT S.P.C	▽ :	▽ :	东莞市箐国电子有限公司																																																																								
8	7	6	5	4	3	2	1																																																																								

[illegible]

8 7 6 5 4 3 2 1

7.0±0.15
4.5±0.15
2.3
16.00±0.2
2.3

7.0±0.15
4.5±0.15
2.3
15.45±0.2
2.3

《 HPDB 》

《 HPCN 》

Entry Hole
10.71±0.3
12.65±0.3

Flat Screw M2.6 (2 Places)
Lower Shield
Spring Latches
Upper Shield
Flat Screw M2.6 (2 Places)
Cable Clipper

QUALITY SYMBOLS
□: ☐ CRITICAL
△: ☒ MAJOR
▽: ☐ ZERO DEFECT
S.P.C

Tolerance
X: ±0.50
x: ±0.30
xx: ±0.25

NAME: SCS1 50P Male ZINC Hood With Latch
REV: A
SCALE: N:1
DATE: 2010/01/09
JINGLI
KING ZHOU

PART NO: BXX-050NN8N3-XX
SPECIFICATION: 02:HPDB
03:HPCN
ENTRY HOLE SIZES: 90:φ9.0
1B:φ11.0

4. SPRING LATCH
3. CABLE CLIPPER
2. FLAT SCREWS
1. BACK SHELL

STAINLESS STEEL
STEEL
STEEL
ZINC ALLOY

PLATING: Ni
PLATING: Ni
PLATING: Ni

REMARKS
PART REMARKS

NAME: BXX-050NN8N3-XX
PART NO.
APP BY
DRAWING NO. BXX-A06

DATE: 2010/01/09
JINGLI
KING ZHOU

东 莞 市 箐 国 电 子 有 限 公 司

8 7 6 5 4 3 2 1