

		8		7		6		5		4		3		2		1																																																																													
F																																																																																													
NOTES: 1. PROTECTION LEVEL: IP67 2. RATED CURRENT: 4 AMP 3. RATED VOLTAGE: 250 V 4. PLUG AND PULL TEST: 500 TIMES MIN.. 5. OPERATING TEMPERATURE: -40℃~+85℃ 6. CONTACT RESISTANCE: ≤3mΩ 7. Connector plug-in conforms to IEC 61076-2-101 8. All materials meet environmental requirements. 9. CABLE CLAMP: ID6.0~8.0mm.																																																																																													
E																																																																																													
D																																																																																													
C																																																																																													
B																																																																																													
<table><tr><td>10</td><td>BACK NUT</td><td>PA</td><td></td><td></td></tr><tr><td>9</td><td>CABLE CLAMP</td><td>PA</td><td></td><td></td></tr><tr><td>8</td><td>A SEAL</td><td>NBR</td><td></td><td></td></tr><tr><td>7</td><td>BACK SHELL</td><td>PA</td><td></td><td></td></tr><tr><td>6</td><td>SCREW</td><td>Stainless steel</td><td></td><td></td></tr><tr><td>5</td><td>Seal ring</td><td>NBR</td><td></td><td></td></tr><tr><td>4</td><td>CONNECTING NUT</td><td>PA</td><td></td><td></td></tr><tr><td>3</td><td>HOOD</td><td>PA</td><td></td><td></td></tr><tr><td>2</td><td>TERMINAL</td><td>COPPER ALLOY</td><td>Au/G/F</td><td></td></tr><tr><td>1</td><td>HOUSING</td><td>PA</td><td></td><td></td></tr><tr><td>ITEM</td><td>DESC.</td><td>MATERIAL</td><td>REMARKS</td><td>PART REMARKS</td></tr><tr><td colspan="2">NAME:</td><td>JAE-10P(F/ANUC) 塑胶壳伺服连接器</td><td>PART NO.</td><td>JAE-10P-VT-HS01</td></tr><tr><td>REV:</td><td>A</td><td>UNIT:</td><td>mm</td><td>DRW BY</td><td>CHK BY</td><td>APP BY</td><td>DRAWING NO.</td></tr><tr><td>SCALE:</td><td>N:1</td><td>DATE:</td><td>2018/03/11</td><td>Huangmei</td><td>Jack Chen</td><td></td><td>JAE-10P</td></tr></table>																		10	BACK NUT	PA			9	CABLE CLAMP	PA			8	A SEAL	NBR			7	BACK SHELL	PA			6	SCREW	Stainless steel			5	Seal ring	NBR			4	CONNECTING NUT	PA			3	HOOD	PA			2	TERMINAL	COPPER ALLOY	Au/G/F		1	HOUSING	PA			ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS	NAME:		JAE-10P(F/ANUC) 塑胶壳伺服连接器	PART NO.	JAE-10P-VT-HS01	REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.	SCALE:	N:1	DATE:	2018/03/11	Huangmei	Jack Chen		JAE-10P
10	BACK NUT	PA																																																																																											
9	CABLE CLAMP	PA																																																																																											
8	A SEAL	NBR																																																																																											
7	BACK SHELL	PA																																																																																											
6	SCREW	Stainless steel																																																																																											
5	Seal ring	NBR																																																																																											
4	CONNECTING NUT	PA																																																																																											
3	HOOD	PA																																																																																											
2	TERMINAL	COPPER ALLOY	Au/G/F																																																																																										
1	HOUSING	PA																																																																																											
ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS																																																																																									
NAME:		JAE-10P(F/ANUC) 塑胶壳伺服连接器	PART NO.	JAE-10P-VT-HS01																																																																																									
REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.																																																																																						
SCALE:	N:1	DATE:	2018/03/11	Huangmei	Jack Chen		JAE-10P																																																																																						
A																																																																																													
<table><tr><td colspan="2">QUALITY SYMBOLS</td><td colspan="2">Tolerance</td></tr><tr><td>□:</td><td>☒:</td><td>x.</td><td>±0.60</td></tr><tr><td>∇:</td><td>MAJOR</td><td>.x</td><td>±0.40</td></tr><tr><td>∇:</td><td>S.P.C</td><td>.xx</td><td>±0.25</td></tr></table>																		QUALITY SYMBOLS		Tolerance		□:	☒:	x.	±0.60	∇:	MAJOR	.x	±0.40	∇:	S.P.C	.xx	±0.25																																																												
QUALITY SYMBOLS		Tolerance																																																																																											
□:	☒:	x.	±0.60																																																																																										
∇:	MAJOR	.x	±0.40																																																																																										
∇:	S.P.C	.xx	±0.25																																																																																										
A		NEW ISSUE		Jack Chen		CRITICAL		MAJOR		ZERO DEFECT		S.P.C		APPROVER		DESCRIPTION																																																																													
SIDE		DATE		7		6		5		4		3		2		1																																																																													